



CSX.0260

QL NANOSIL RAINPROOF

Water and oil repellent treatment
for absorbent floors

Dosage

0.03 - 0.07 l /m²
(Recommended: 0.05 l /m²)

Packaging

- Plastic can 5 l
- Plastic can 25 l

Application

- Low pressure airless nebulizer
- Brush
- Paint roller
- Sprayer

Family
Consilex

Product Lines

- Building
- Infratech

Type

Water-based siloxane solutions

Functional Categories

- Construction of high performance industrial concrete floors
- Waterproofing treatments of plasters and masonry
- Wall structure treatments and repair of industrial concrete floors
- Prefabrication
- Curing compounds for industrial floors, screeds and concrete in general
- Construction of concrete floors with the technique of the 'washed gravel'

Components
Single-component

Appearance
Liquid

General description

QL NANOSIL RAINPROOF is a product in aqueous solution, with high performance fluorinated silane-siloxane polymers, designed to be a greater repellent to water and oil on all absorbent concrete and masonry surfaces, indoors and outdoors.

QL NANOSIL RAINPROOF is non-toxic, odourless, non-flammable and very simple to use.

QL NANOSIL RAINPROOF has a small molecular structure (0.029 micron) that allows in-depth penetration of the surfaces without modifying the appearance and shine; it offers excellent resistance to water and oil and is resistant to stains caused by spilling oil and seed oil, coffee, ketchup, mustard and other foodstuff substances.

QL NANOSIL RAINPROOF reduces the damage caused by frost - defrost and saline efflorescence. Surfaces treated with QL NANOSIL RAINPROOF have no film or surface film. The life expectancy planned for the treated surface is approx. 5 - 10 years (based on the application and use).

General features

It is an odourless, waterproof, oil repellent and stain-proof product for surfaces in concrete and masonry work both for indoors and outdoors. It has exclusive new generation technology formulated on the basis of three different polymers: Silanes, siloxanes and fluoropolymers. It is water based, does not contain solvents and has very low COV emissions.


Fields of application

QL NANOSIL RAINPROOF is a primer used as a water and oil repellent for absorbent surfaces such as concrete, brick, masonry and stone, including: architectural concrete floors in washed gravel, surfaces in concrete, footpaths, blocks in concrete, reconstructed stone, moulded concrete, blocks, road manufactured works in concrete in general.


Available colours

- Amber

Basic features

 Density:
1.09 kg/dm³

 Nonflammable

 Use wearing protective glasses

 Use wearing protective gloves

Technical specifications

Boiling point/range: 100 °C

pH: 11 _

IF YOU WANT TO SOLVE IT
 azichem

www.azichem.com

Updated: **24/02/2018**
General sales conditions and legal
notices on
www.azichem.com/disclaimer

Tools cleansing

- Water

Applicable on

- Concrete
- Bricks
- Mixed walls (bricks and stones)
- Brickworks
- Stone walls
- Rock walls
- Porphyry and natural stones

Instructions for use

1. Apply the product on concrete surfaces after at least 7 days from completion of the cast
2. Do not apply QL NANOSIL RAINPROOF on surfaces with a temperature under 5°C.
3. Do not apply outside if raining or snowing.
4. QL NANOSIL RAINPROOF must be applied with a low pressure spray, airless sprayer, roller or brush. Apply 1 litre per 5 to 10 m². Consumption varies based on the porosity of the surface.
5. Apply one or more coats based on the surface porosity. Apply the second coat "fresh on fresh", when the first is not yet dry. The drying time time depends on the atmospheric conditions (temperature, humidity, wind, etc.).
6. Do not leave excess product on the surface. Remove the excess product with a clean cloth before drying.
7. On some surfaces with few pores (as marble and granite) spray the surface with clean water before applying QL NANOSIL RAINPROOF. This procedure opens the substrate pores and makes penetration of the product easier.
8. On vertical surfaces, always apply the product from the base upwards.
9. Clean the equipment with water.

Maximum protection is reached after 3-6 days of treatment.

Substrate preparation

You are advised to do a test application on a small piece to identify suitability of the product and the result. Leave the surface to dry before application.

1. The surface of the works to treat must be clean, structurally safe and free of wax, dirt, coatings, paint, seasoning agents and chemical residue.
2. Cracks, control joints and construction joints must be adequately prepared and sealed. Cement residue must be removed.
3. Remove dust before applying QL NANOSIL RAINPROOF
4. The concrete surface smoothed with a trowel must be tested in advance to view the penetration capacity and to estimate consumption.
5. Before application, carefully cover and protect windows, frames and any surface that can accidentally come in contact with the product. In the event of a leak, clean with water immediately.

Storage and preservation

Protect from freezing. Store the product in its original packing, in a fresh and dry environment, avoiding frost and direct sunlight. Inadequate storage of the product may result in a loss of rheological performance. Store the product at a temperature between +5°C and +35°C.



www.azichem.com

Updated: **24/02/2018**
General sales conditions and legal
notices on
www.azichem.com/disclaimer

Warnings, Precautions and Ecology

Technical and performance data outlined in this document are the result of laboratory testing conducted in a conditioned environment, as such they can result as considerably changed from operating and application conditions. The need follows to carry out preliminary tests in actual use conditions.

The user is required to check the product's most recent Material Safety Data Sheet, reporting physical-chemical and toxicological data, risk phrases and other useful information on how to safely transport, use and dispose of the product and its packaging. It is also reminded that the product and its packaging must not be dispersed in the environment for any reason.

Remember that the user is obliged to read the most recent safety data sheet for the product, containing the chemical-physical and toxicological data, the risk phases and other information to transport, use and dispose of the product and its packaging in complete safety. You are however reminded not to dispose of the product and its packaging in the environment. You are not advised to use it on horizontal surfaces outdoors or surfaces subject to rainfall. Keep away from open flames and heat sources, do not smoke during application, use with safety gloves and goggles.

QL NANOSIL RAINPROOF is produced/distributed by



Via Giovanni Gentile, 16/A - 46044 Goito (MN), Italy
info@azichem.com Tel. +39 0376.604185 /604365 Fax +39 0376 604398



www.azichem.com

Updated: **24/02/2018**
General sales conditions and legal
notices on
www.azichem.com/disclaimer