



PRS.0092

PROBAND

Butyl rubber-based self-adhesive waterproofing strap

Customs Code

3919 1015

Packaging

- Roll 10 m

Application

- Apply by hand

Family
Proseal

Product Lines

- Aqua
- Building
- Infratech

Components
Single-component

Type
Butt-straps, bars and plastic profiles

Functional Categories

- Osmotic waterproofing
- Waterproofing with hot-sprayed elastomeric coatings (100% pure polyurea)
- Waterproofing control joints or construction joints
- Horizontal cement waterproofing of terraces and balconies

Appearance
Tape

General description

Cold applied water-repellent adhesive tape, composed of a layer with visco-elastic butyl rubber consistency, coated with a polypropylene non-woven fabric, for elastic waterproofing of non-structural joints in balconies, terraces, etc. Size of the strap: 80 mm x 0.9 mm.

General features

The PROBAND non-woven fabric coating is composed of 100% pure polypropylene fibres, with a weight of 30 g/m² and a tensile strength of 45 N.

Dosage

1.1 m/m: 1 metre of PROBAND for each linear metre, being careful to overlap the rolls of approximately 5-10 cm in correspondence with the edges of the band.

Fields of application

Elastic waterproofing of non-structural joints in balconies and terraces, especially in the protective "kerb" of the connection joints between the screed and the vertical wall.

Basic features



Nonflammable



Shelf-life:
12 months



Temperature of use:
+5 / +40 °C



Use wearing protective gloves



UV-resistant



Width:
8 cm



Available colours
Gray

Technical specifications

Unit weight: 30 g/m²

Working temperature: -30 / +80 °C

Substrate preparation

The application supports must be clean, dry, undamaged, cohesive, free from fouling and dust.

IF YOU WANT TO SOLVE IT
 **azichem**

www.azichem.com

Updated: **24/08/2020**

General sales conditions and legal notices on

www.azichem.com/disclaimer

Instructions for use

The strap is provided with a special waxed paper film on the adhesive side. To apply, proceed with the detachment of the protective film and place the strap in its final place, with the adhesive side facing the support. Apply slight pressure with your hand to ensure proper adhesion to the support. Then continue to detach the protective film while unwinding of the roll and setting on site, taking care to avoid the formation of bubbles.

Storage and preservation

Store the product in its original packing, in a fresh and dry environment, avoiding frost and direct sunlight. Store the product at a temperature between +5°C and +35°C.



Warnings, Precautions and Ecology

The general information, along with any instructions and recommendations for use of this product, including in this data sheet and eventually provided verbally or in writing, correspond to the present state of our scientific and practical knowledge.

Any technical and performance data reported is the result of laboratory tests conducted in a controlled environment and thus may be subject to modification in relation to the actual conditions of implementation.

Azichem Srl does not assume any liability arising from inadequate characteristics related to improper use of the product or connected to defects arising from factors or elements unrelated to the quality of the product, including improper storage.

Those wishing to utilise the product are required to determine prior to use whether or not the same is suitable for the intended use, assuming all consequent responsibility.

The technical and characteristic details contained in this data sheet shall be updated periodically. For consultation in real time, please visit the website: www.azichem.com. The date of revision is indicated in the space to the side. The current edition cancels out and replaces any previous version.

Please note that the user is required to read the latest Safety Data Sheet for this product, containing chemical-physical and toxicological data, risk phrases and other information regarding the safe transport, use and disposal of the product and its packaging. For consultation, please visit: www.azichem.com.

It is forbidden to dispose of the product and/or packaging in the environment.

Butyl mastics are extremely sensitive to the action of solvents.

It is recommended to coat PROBAND, once placed, with elasto-plastic cement mortars or similar products (OSMOCEM FLEX, OSMOCEM D, SYNTECH POLYUREA SPRAY 400).



www.azichem.com

Updated: **24/08/2020**
General sales conditions and legal notices on www.azichem.com/disclaimer

PROBAND is produced/distributed by



Via Giovanni Gentile, 16/A - 46044 Goito (MN), Italy
info@azichem.com Tel. +39 0376.604185 /604365 Fax +39 0376 604398



www.azichem.com

Updated: **24/08/2020**
General sales conditions and legal
notices on
www.azichem.com/disclaimer

Page: **3/3**